





# BOREALIS

DESCRIPTION: Slab TEXTURE: Klean-Bloc Wood

## Pallet Overview - 5 x 30



## Pallet Overview - 10 x 30



Klean-Bloc Wood  
Smoked Pine  
Klean-Bloc Wood  
Hazelnut Brandy  
Klean-Bloc Wood  
Riviera

### 5" x 30"

#### Specifications per pallet



68 units / pallet

	Imperial	Metric
Product dimension (L x W x H)	30 x 5 x 2 1/4	762 x 127 x 57
Cubing	70.83 ft <sup>2</sup>	6.58 m <sup>2</sup>
Units	1.04 ft <sup>2</sup>	0.10 m <sup>2</sup>
Approx. Weight	1 784 lbs	809 kg
Number of rows	4	
Coverage per row	17.71 ft <sup>2</sup>	1.65 m <sup>2</sup>
Lin. coverage per row	Depth: 7.08 lin. ft Length: 42.5 lin. ft	2.16 lin. m 12.96 lin. m

### 10" x 30"

#### Specifications per pallet




34 units / pallet


	Imperial	Metric
Product dimension (L x W x H)	30 x 10 x 2 1/4	762 x 254 x 57
Cubing	70.83 ft <sup>2</sup>	6.58 m <sup>2</sup>
Approx. Weight	1 881 lbs	853 kg
Number of rows	2	
Coverage per row	35.42 ft <sup>2</sup>	3.29 m <sup>2</sup>
Lin. coverage per row	Depth: 42.5 lin. ft Length: 14.2 lin. ft	12.95 lin. m 4.33 lin. m

## Laying Patterns Options


01 | Linear




02 | Linear




03 | Linear




04 | Linear



05 | Herringbone



06 | Linear



## NOTES

Palletized upright.

See page 6 for icons description.

See page 26 for more information about applications.

See page 34 to 36 for more technical information.

\*For an authentic look, each color option is composed of a variety of darker & lighter tones. Natural ingredients

such as granite are present within the recipe to allow for a range in tones, veining and textures from one stone to another.

In order to obtain a more realistic appearance to natural stone, wet cast (Stonedge collection) slabs are intended to have a slightly larger variance in their dimensions than dry cast slabs. See Notes for dimensional tolerances on page 34.

**IMPORTANT:** When installing Borealis 5 x 30 or Borealis 10 x 30, it is recommended to have a gap between 1/16 and 3/16 in. (2 and 5 mm), between the units, to allow the sand to enter between each unit.

Please note that for barefoot walking areas (e.g. pool deck) dark-colored paving units could get very hot under the sun.

Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.