

Lafitt® Plus Capping and Step

Capping	Metric (mm)	Imperial (in.)
	90 x 305 x 400	3 9/16 x 12 x 15 3/4
Weight/unit	26.97 kg	59.4 lb
Units/length	2.50 units/lin. m	0.76 unit/lin. ft
Length/row	2.40 lin. m	7.88 lin. ft
Length/cube	21.60 lin. m	70.88 lin. ft
Qty/cube	54 units 9 Rows	54 units
Weight/cube	1456 kg	3210 lb

Code	Colour
16253731	Range Margaux Beige
16253724	Range Newport Grey
16253722	Range Scandina Grey
16253723	Rockland Black


Production location	Metcalfe
Can be double stacked	
Sold in full cubes	

Step	Metric (mm)	Imperial (in.)
	90 x 400 x 400	3 9/16 x 15 3/4 x 15 3/4
Weight/unit	35.69 kg	78.6 lb
Length/cube	14.40 lin. m	47.25 lin. ft
Qty/cube	36 units 9 Rows	36 units
Weight/cube	1285 kg	2830 lb


Code	Colour
16253704	Range Margaux Beige
16253703	Range Newport Grey
16253702	Rockland Black
16253701	Range Scandina Grey

Production location	Metcalfe
Can be double stacked	
Sold in full cubes	

Typical Row



Typical Row



Technical Information

Product	Lafitt Plus Capping
Standard	ASTM C 1372
Flexural Strength	N/A
Compressive Strength	20.7 MPa
De-icing salts freeze-thaw durability	N/A
Density	2000 kg/m ²
Absorption	10.4%
Dimension Tolerance*	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm



Technical Information

Product	Lafitt Plus Step
Standard	N/A
Flexural Strength	N/A
Compressive Strength	35 MPa
De-icing salts freeze-thaw durability	500 g/m ²
Density	2250 kg/m ²
Absorption	5%
Dimension Tolerance*	Length: ±2.0 mm Width: ±2.0 mm Height: -2.0 to +1.0 mm



Additional details: See our landscaping installation guide on our website.