

Melville® 60 Small Rectangle Paver


	Metric (mm)	Imperial (in.)
	60 x 190 x 380	2 3/8 x 7 1/2 x 15
Weight/unit	10 kg	22 lb
Area/unit	13.89 units/m ²	1.29 units/ft ²
Area/layer	0.87 m ²	9.33 ft ²
Area/cube	10.44 m ² 12 Rows	111.96 ft ²
Length/row	4.57 lin. m	15.00 lin. ft
Length/cube	54.86 lin. m	180.00 lin. ft
Qty/cube	144 units	144 units
Weight/cube	1431 kg	3154 lb

Code	Colour - Prestige
12053044	Range Amber Beige
12052446	Rockland Black
12052448	Range Scandina Grey
	Colour - Standard
12053043	Range Shaded Grey


Production location	Montreal, Quebec and Metcalfe
Can be double stacked	
Sold in full cubes	

1 bag of Techniseal sand covers approx.: 147 ft²


Typical Row



Laying Pattern



Linear



Herringbone



Technical Information

Product	Melville 60 Small Rectangle Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Melville 60 Slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.